



OneWrapPlus

The stretch wrapper that gives a "plus" to your production

SIAT OneWrapPlus is the new Siat machine that will allow you to maximize the results of your wrapping activity.

Drawn on the strong mechanical structure of Siat machines, it has an intuitive control panel that will make it easy to program it!



SIMPLE TO USE, COMPLETE IN FUNCTIONALITY

"Thanks to the icons on the control panel it is extremely **quick** to set a complete wrapping program that will optimize the film applied to all the different SKU you might need to wrap.

This is not the only "Plus" of the machine: it has a very robust structure and the guarantee of a **2400 kg maximum weight** for the platform (excluding HSD platform). Your business would be purchasing a reliable and **high-quality** device!

Moreover, with up to **10 customizable wrapping programs** that can be recorded, the operator will only have to program the OneWrapPlus once, and then simply recall the desired wrapping program from the control panel when required."





A SAFETY DRIVEN SOLUTION

"Siat likes to remind that in an industrial environment **safety** is always a leading topic. For this reason, all of our machines ranges are designed focusing maximum attention to the safety equipment on the unit.

Anti-fall device and a safety plate

under all versions of film carriage are fitted as standard, as well as many others safety features. Your machine will always be efficient thanks to the new possibility to upgrade the software version by simply inserting a USB key into the control board.

CONFIGURATIONS

Feature	Available configurations			
Platform	1650	1800	2200	1650 HSD
Mast	2200	2600	3000	
Carriage	М	FM	SM	LP
Carriage prestretch level (only LP)	150%	200%	250% (std)	300%
Photocell	Available as option			
Cutting system on LP carriage	Available as option			

OPTIONALS

- » Ramp for all the platforms sizes;
- » Pit frame;
- » Lifting frame;
- » Weighing system;
- » Pressing unit.

AVAILABLE CARRIAGES:



Simple functioning;

- » Manually adjustable lay-on force/tension;
- » Purely mechanical relationship between film regulation and applied tension;
- » Quick and easy to set;
- » Film reel weight has no impact on the brake/tension control.



AIR PRESSURE REQUIREMENTS				
Compressed air min. pressure	6 bar			
Compressed	Pressing unit height (mm)	Flow consumption for cycle (I)		
air flow	2200	9		
	2600	12		
	3000	14		



FM

Simple functioning;

- » Better control on applying force to the stretching roll;
- » The machine is able to record different programs with different settings;
- » Application of the brake control on an different roll - instead of the coil holder- no influence of the coil weight.
- » Break regulation from control panel



First pre-stretch concept applied;

- » Gear box pre-stretch system for an reliable but still basic approach;
- » Pre-stretch setting by an included set of different gears (30-60-90 % pre-stretch)
- » Mechanical pre-stretch



Powered pre-stretch carriage;

- » Reliable pre-stretch up to 250% and 300%
- » Adjustable pre-stretch
- » Possibility to record and save different programs - easy and fast setting-
- » Improved stability of the load thanks to the most reliable pre-stretch value
- » No-cut pre-stretch rolls
- » Dancing Roller to follow the variation in the needed film tension



SIAT Spa

Via Puecher 22, 22078 Turate - Como

www.siat.com www.shop.siat.com



ging and produces more than 17,000 machines per year, and has done since 1970. Our product range includes semi-automatic as well as fully automatic machines like Case Sealers and Case Erectors, Stretch Wrappers, Strapping Tools / Machines, Flexographinc Printing Machines and Tape Dispensers. The company is present in more than 100 countries and is constantly investing worldwide to meet customers

FOLLOW US



